




- Stable FBG P&T gauge
- No downhole electronics
- Long life at elevated temperature
- High multi-drop capability
- Low Cost

SmartCell is a fibre Bragg grating based sensor that can measure highly varying pressure and temperature excursions in production and observation wells. Numerous SmartCell sensors can be connected on a single optical fibre cable and interrogated with a topside instrument. The instrument can be located remote from the wellhead, and simultaneously monitor SmartCell chains deployed in numerous wells, providing for a highly cost effective tool for intelligent reservoir management and optimisation.

With the support of a major Oil & Gas Company, Smart Fibres' FBG sensing experts have spent over 5 years optimising the design of SmartCell, qualifying its performance with extensive laboratory testing:



Presented below are current product specifications, and expected capabilities of the planned extended range of SmartCell products:

Specifications

Parameter	SmartCell Capability
Pressure Measurement	Annulus only
Working Pressure Range (psi)	Atmospheric to 5,000 ps
Overload Pressure	7500psi (150 %FS)
Working Temperature Range	0 °C to 150 °C
Pressure Accuracy(psi) ¹	0.1 %FS
Pressure Resolution (psi)	0.05 %FS
Temperature Accuracy °C	0.1 °C
Temperature Resolution °C	0.001 °C
Pressure Measurement Stability ²	± 0.05 %FS/year
Max number of Gauges per Cable	10
Dimensions (mm) without splice housings	55 x 20 x 120
Dimensions (mm) with splice housings	55 x 20 x 300
Service	H ₂ S in accordance with ISO 15156

1. As calibrated, over all pressure and temperature range, expressed as one standard deviation of the absolute errors.

2. Stability at 80% FSD pressure and 60 degC over 1 year, expressed as one standard deviation. No long-term trend visible in stability test data.

Smart Fibres maintains a policy of continuous improvement so specifications may change without notice.

SmartCell measures annulus pressure, for which the gauge carrier is a low cost, simple to install clamp, which secures the gauge to the tubing string and protects it during run-in hole.

A SmartCell mandrel for tubing and dual annulus/tubing measurements will be developed in the future




The first installation of a fiberoptic distributed pressure and temperature sensing system involved a string of 9 SmartCell P/T gauges measuring annulus pressure in a vertical observation well in Oman in 2008. The image below shows how this system is configured.



Solar powered surface interrogator radios data to Muscat HQ



SmartCell® attachment to tubing string



High quality P/T data is being delivered via wireless communication to the Operator's Muscat headquarters, where PTs are monitoring the fluid levels in the wellbore. For more information about SmartCell and Distributed P/T Sensing, visit www.smartfibres.com/SmartCell_DPTS.htm

Smart Fibres' downhole products are marketed through **TENDEKA**. Please contact alan.sanderson@tendeka.com for more information.