









X . X

UNLESS OTHERWISE STATED

NOTES:

A.ALLOW FOR 80MM EXTRA LENGTH FOR MATED
CONNECTORS AND FIBRE BEND RELIEF RADIUS.
2.UNIT SUPPLIED WITH 4 OFF 1/4" UNF BOLTS AND 4 OFF 1/4"
UNF NUTS,FOR FIXING PURPOSES.

						MA
В	GJ	ОВ	CBS	CHANGED THE LENGTH OF ASSEMBLY WITH MATED USB FROM 240 TO 230.	Mar-12-12	
А	GJ	ОВ	KMJ	FIRST ISSUE	Feb-29-12	T
ISSUE	DRWN	СНК	APPD	MODIFICATION	DATE	
ALL RIGHTS, TITLE AND INTEREST IN THIS DOCUMENT ARE AND SHALL REMAIN VESTED IN SMART FIBRESLTD AND THIS DOCUMENT IS NOT TO BE USED, COPIED COMMUNICATED OR DISCLOSED IN WHOLE OR IN PART TO ANY PERSON EXCEPT IN ACCORDANCE WITH AN AGREEMENT IN WRITING WITH SMART FIBRES LTD.						

ATERIAL:	N / A	
OLERANCES:		USED ON: 7049
V	mm + 0.5	



 $mm\pm0.25$ SCALE: NΑ $X . X X mm \pm 0 . I$ FINISH: CLEAN

SMARTSCAN AERO ASSEMBLY

7049-2010

SIZE: А3